



WEST FELICIANA

WEST FELICIANA PARISH

Culvert Permit Application

Applicant _____ Phone # _____ Email _____

Property Address _____

Driveway Roadside Ditch Enclosure (requires a plan for approval)

Width of Proposed Culvert _____ Material _____

All culverts shall be installed according to the attached parish standards.

A site inspection to determine pipe size will be conducted after the Public Works Road Superintendent accepts this application.

All work shall be inspected prior to covering.

I hereby certify that I have read and examined this application and know the same to be true and correct. All provisions of laws and ordinances governing this type of work will be complied with whether specified herein or not. The granting of a permit does not presume to give authority to violate or cancel the provisions of any other State or Local law regulating construction or the performance of construction.

(Signature of Applicant)

(Date)

Call West Feliciana Parish Maintenance Barn for All Inspections: (225) 784-3721

Fee: **\$25.00**

Accepted:

Cash _____

Check _____

Inspector

(Date)

Inspected by: _____

Date: _____

Approved: _____

Not Approved: _____

Comments: _____



WEST FELICIANA PARISH

WEST FELICIANA

Driveway Culvert and/or Roadside Ditch Enclosure Standard and Procedure

Any driveway culvert or roadside ditch enclosure (work) on a road maintained by the parish must conform to an approved Construction Plan or Final Plat for a recognized subdivision. If no such plan or plat exists, or it exists yet lacks specificity for such work, the Public Works Department will specify sizes and materials.

All work must be inspected prior to being covered up (fee for the inspection is \$25).

Bedding and backfill of the work shall be in accordance with the attached standard plan, 701-01.

Driveways

Address must be posted, and proposed driveway marked to insure correct location.

Culverts for all non-paved driveways (gravel, limestone, sand, silt, dirt, etc.) will be metal or concrete. Plastic may be allowed only if concrete end treatments or headwalls are installed and there is at least 12" of cover. No pipe diameter under 15" is permitted.

Culverts for all paved driveways (asphalt or concrete) will be metal or concrete. Plastic may be allowed under paved driveways only if concrete end treatments or headwalls are installed.

Culvert shall be installed a minimum of 5' from the edge of the roadway. Minimum width is 12'. Maximum width is 24'. Pipe length shall extend 12" beyond the driveway width.

Driveway should slope away from roadway when possible and have 3:1 slope or larger at pipe ends.

Roadside Ditch Enclosures

All roadside ditch enclosure applicants must submit a plan for approval. This plan shall include:

- Directional arrow
- Property line
- Right of way

Pipe materials shall be concrete or metal. Plastic may be used provided there is 18" of cover available.

No sheet flow from the lot will be allowed into the roadway. All drainage from the lot must be collected on the site and directed into the proposed system.

Inlets shall be required at a maximum spacing of 50' and must have a minimum opening of 384 in² (18" x 18").

Until vegetation is established over the enclosed ditch, owner shall keep inlets and pipes free from silt, dirt, and debris.

Owner will be required to execute a Hold Harmless Agreement with the parish for any work described herein.